



UTL[®] 中国·尤提乐电气有限公司
CHINA UTILITY ELECTRICAL.,LTD.



PRODUCTS

HEAVY DUTY CONNECTORS

重载连接器

科技·品质·生活





CONTENT

目录

如何订购	01
产品选型指南	02
导线压接类型总览	04
电缆接头的选择	05
芯件导轨安装支架	06
UTL-HA接插体系列	07
UTL-HE接插体系列	14
UTL-HEE接插体系列	27
UTL-HD/UTL-HDD接插件系列	32
UTL-HSB接插体系列	38
UTL-HK插体系列	42
冷压针及对应工具	44
编码销(导向销)	45
接插体	46
成套组合	48

PEOPLE

-ORIENTED

TECHNOLOGY INNOVATION

以人为本，科技创新

坚持以人为本的理念
在生产发展过程中
注重员工的知识水平和业务能力
有计划有组织地开展各项培训工作
不断地提高学习和创造能力
以科技为发展的动力
在原有的基础上
致力于各项产品的研发和创新



How to order
如何订购

订购接插件的步骤如下

1. 接插体公插

公插接线形式有：螺钉压接、冷压针压接（冷压针需要单独订购）和弹片压接形式。

2. 接插体母插

母插接线形式有：螺钉压接、冷压针压接（冷压针需要单独订购）和弹片压接形式。

3. 防护外壳上壳

外壳上壳形式有：低结构或高结构、侧面或顶部出线、2耳或4耳、单扣或双扣形式。

4. 底座

开孔安装底座：带或不带保护盖、单扣或双扣形式。
表面安装底座：低结构或高结构、带或不带保护盖、2耳或4耳、单扣或双扣、1个或2个出线孔形式。

5. 电缆进线保护

带单层或多层密封圈的平口接头
金属或塑料电缩接头
特殊电缆保护附件

6. 其他附件

各种类型的金属及塑料保护盖、编码销、导柜安装框架。

For a complete connector components may be order from the following sub headings

Mala insart

Male insert with screw terminal, crimp terminal (order contacts separately) or cage-clamp terminal.

Female insert

Female insert with screw terminal, crimp terminal(order contacts separately) or cage-clamp terminal.

Hoods

Hoods with low or high construction, side or top cable entry, 2 or 4 bolts, 1 or 2 locking lovers.

Housings

Bulkhead mounting housings with orwithout protection cover, 1 or 2 locking levers.
Surface mounting housings with low or high construction, with or without protection cover, 2 or4 bolts, 1 or 2 locking levers,l or 2 cable entries.

Cable entry protection

Cable glands with normal or multiple sealing.
Metal or plastic cable glands.
Special cable entry protection or extensive range of accessorles.


Accessories.

Protection cover available, code and guide pins for coding inserts fixing screws for use without hoods and housings.

防护外壳型号说明 List of hoods and housings

UTL	-	H24B	-	SGR	-	LB	-	PG21
								PG21 螺纹 PG21 Thread
								单扣 singalocking lawr
								表面安装底座 Surface mounting housing
								系列 Series
								企业代号 Enterprise code
AG	→							双扣，开孔底座 Bulkhead mounting housing
AG-LB	→							单扣，开孔底座 Buikhead moounting housing with single locking lever
AD	→							4耳，带盖开孔底座 Bulkhead mounting housing with cover, bolts
-BO	→							单扣，带盖开孔底座 Bulkhead moounting housing with cover, single locking lever
AD-LB	→							双扣，表面安装底座 Surfaceimounting housing
SGR	→							高结构带盖表面安装底座 Surface mounting housing with cover
SDRH	→							4耳，侧出上壳 Side entry hood
TS	→							4耳，高结构侧出上壳 High construction side entry hood
TSH	→							4耳，顶出上壳 Top entry hood
TG	→							4耳，高结构顶出上壳 High contruction top entry hood
TGH	→							双扣，侧出上壳 Side entrydOUBLElOCKing leverhood
TSB	→							双扣，顶出上壳 Top entry, double locking lever hood
TGB	→							双扣，顶出上壳 Top entry, double locking lever hood
TBF	→							双扣，电缆对接下壳 Cable coupler hood

接插件安装示意图 Assembly details



Selection guide
产品选型指南

在选择插件时，需要


- 额定电压电流
- 回路数【接插件针数】
- 外壳形式（防护外壳上壳及底座的选择）
- 附件（主要为电缆接头的选择）

When selecting heavy duty connector,we meed to choose as follow


- Rated voltage and current
- Palesof connector
- Chaosing hood and housing type
- Accwssories(selecting cable gland)

产品型号说明 Type explanation

例：UTL-HE-016-M为UTL-HE系列的16针公接插体。
i.e.:UTL-HE-016-M means male insert of 16 poles in UTL-HEseries



重载接插件常用套件组合示意图如下 Set general overview



注：以上所有规格均提供单扣形式。
All sets shown above with one lever types.

Selecting Cable Glands
电缆接头的选择

UTL-PG 制电缆接头的选择 Selecting PG Cable Glands
The UTL-PG sizes indicated are intended for standard cables

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing. Rows include 0.5 mm², AWG 20, 10, 16, 24, 30, 35, 40, 61.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing. Rows include 0.75 mm², AWG 18, 10, 18, 28, 32, 40, 50, 61.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing. Rows include 1 mm², AWG 16-18, 10, 16, 24, 34, 48, 61.

公制电缆接头的选择 Selecting Metric Cable Glands
The Metric-sizes indicated are intended for standard cables
Please observe the clamping range of your choice of metric cables glands.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing. Rows include 0.5 mm², AWG 20, 10, 16, 24, 35, 40, 61.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing16. Rows include 0.75 mm², AWG 18, 10, 18, 25, 32, 40, 50, 61.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing. Rows include 1 mm², AWG 16-18, 10, 16, 24, 34, 48, 61.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing. Rows include 1.5 mm², AWG 16, 11, 16, 25, 32, 42, 50, 61.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing. Rows include 2.5 mm², AWG 16, 7, 11, 16, 18, 25, 34, 50.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing. Rows include 4 mm², AWG 10-12, 5, 7, 11.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing. Rows include 1.5 mm², AWG 16, 11, 16, 25, 32, 42, 61.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing16. Rows include 2.5 mm², AWG 12-14, 11, 16, 25, 34, 50, 61.

Table with 4 columns: 导线截面 Cross-sec., 导线条数 No.of.cond., 电缆范围 CableΦ approx., 适用的电缆接头 Metric with multi-layer sealing. Rows include 4 mm², AWG 10-12, 5, 7, 11.

Insert mounting element
芯件导轨安装支架

用于将连接体横向固定在常用的标准导轨上






Table with 2 columns: 型号 /type, 套件订购 /Set order. Rows include 6B, 10B, 16B, 24B.

Table with 8 columns: 尺寸 /Size, A, B, C, D, E, F, G. Rows include 6B,10B,16B and 24B.






UTL-HA 系列 3 回路接插件套件 UTL-HA series 3 Poles of connector




工作电流：16A
工作电压：400/500V
阻燃等级 (据 UL94): VO
防护等级：IP65
接线形式：螺钉压接
弹片压接
电缆人口可选螺纹：
M20, PG11
Rated current: 16A
Rated voltage: 400/500V
Flammability acc.to UL94: VO
Degree of protection acc to
DIN40 050: IP65
Terminal: Screwterminal
Spring terminal
Thread: M20 , PG11



配套外壳 Suit hood/housing




UTL-HA-016-F 锁扣有普通金属锁扣和塑料保护盖

			
UTL-H16A-TSH-RO	UTL-H16A-TGH-RO	UTL-H16A-TSH-RO	UTL-H16A-TGH-RO
			
UTL-H16A-AG-LB	UTL-H16A-AG-LB	UTL-H16A-SGR-LB	UTL-H16A-SGR-LB
UTL-HDC-HA-016-1	UTL-HDC-HA-016-2	UTL-HDC-HA-016-3	UTL-HDC-HA-016-4
侧面进线 /Side entry	正面进线 /Top entry	侧面进线 /Side entry	正面进线 /Top entry
			
UTL-H16A-TSH-RO	UTL-H16A-TGH-RO	UTL-H16A-TSH-RO	UTL-H16A-TGH-RO
			
UTL-H16A-AD-LB	UTL-H16A-AD-LB	UTL-H16A-SDR-LB	UTL-H16A-SDR-LB
UTL-HDC-HA-016-1DB	UTL-HDC-HA-016-2DB	UTL-HDC-HA-016-3DB	UTL-HDC-HA-016-4DB
侧面进线 /Side entry	正面进线 /Top entry	侧面进线 /Side entry	正面进线 /Top entry


UTL- H16A 上壳 / 底座 UTL- H16A hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
外壳上壳：侧面进线 Hood:Side entry			
	PG16 PG21	UTL-H16A-TSH-RO-PG16 UTL-H16A-TSH-RO-PG21	
外壳上壳：顶部进线 Hood:Top entry			
	PG16 PG21	UTL-H16A-TGH-RO-PG16 UTL-H16A-TGH-RO-PG21	
外壳底座：开孔安装 Surface mounted:mounted			
 		UTL-H16A-AG-LB UTL-H16A-AD-LB	
外壳底座：表面安装 Surface mounted:Side entry			
 	PG16 PG21 PG16 PG21	UTL-H16A-SGR-LB-PG16 UTL-H16A-SGR-LB-PG21 UTL-H16A-SDR-LB-PG16 UTL-H16A-SDR-LB-PG21	




UTL-HA 系列 32 回路接插件套件 HA series 32 Poles of connector




工作电流：16A
工作电压：400/500V
阻燃等级（据 UL94）：VO
防护等级：IP65
接线形式：螺钉压接
弹片压接
电缆入口可选螺纹：
PG21，PG29
Rated current: 16A
Rated voltage: 400/500V
Flammability acc. to UL94: VO
Degree of protection acc. to DIN40 050: IP65
Terminal: Screw terminal
Spring terminal
Thread: PG21，PG29





配套外壳 Suit hood/housing



UTL-HE 系列 6 回路接插件套件 HE series 6 Poles of connector



工作电流：16A
工作电压：400/500V
阻燃等级（据 UL94）：VO
防护等级：IP65
接线形式：螺钉压接
弹片压接
冷压针压接
电缆入口可选螺纹：
M20，PG16，PG21
Rated current: 16A
Rated voltage: 400/500V
Flammability acc. to UL94: VO
Degree of protection acc. to DIN40 050: IP65
Terminal: Screw terminal
Spring terminal
Crimp terminal
Thread: M20，PG16，PG21






配套外壳 Suit hood/housing

UTL-H6B 上壳 UTL-H6B hood	螺纹 Thread	型号 Type	图纸 Drawing
----------------------------	--------------	------------	---------------

外壳上壳：侧面进线
Hood:Side entry




PG13.5 UTL-H6B-TS-RO
PG16 PG13.5
M20 PG16
M20 M20






PG13.5 UTL-H6B-TS-RO
PG14 PG13.5
M20 PG16
M20 M20





高结构 /High construction
UTL-H6B-TS-RO
PG21 UTL-H6B-TS-RO
PG29 PG13.5
M25 PG16
M20 M20




UTL-H6B 底座 UTL-H6B housing	螺纹 Thread	型号 Type	图纸 Drawing
-------------------------------	--------------	------------	---------------

外壳底座：开孔安装
Bulkhead:mounted




UTL-H6B-AG-6B






带保护盖
With protection covers
UTL-H6B-AD-LB



外壳上壳：顶部进线
Hood:Top entry




PG13.5 UTL-H6B-TG-RO
PG16 PG13.5
M20 PG16
M20 M20





高结构 /High construction
UTL-H6B-TGH-RO
PG16 UTL-H6B-TGH-RO
PG21 PG16
PG29 PG21
M20 PG29
M20 M20






PG13.5 UTL-H6B-TG-RO
PG16 PG13.5
M20 PG16
M20 M20



外壳底座：表面安装
Surface mounted:Side entry



PG13.5 UTL-H6B-SGR-LB
PG16 PG13.5
M20 PG16
M20 M20






外壳底座：表面安装
Surface mounted:Side entry






带保护盖
With protection covers
UTL-H6B-SGR-LB
PG13.5 UTL-H6B-SGR-LB
PG16 PG13.5
M20 PG16
M20 M20







UTL-HE 系列 10 回路接插件套件 HE series 10 Poles of connector



UTL-HE-010-M



UTL-HE-010-F



UTL-HE-010 有普通金属单扣和塑料保护盖
UTL-HE-010 有普通金属双扣和塑料保护盖

工作电流：16A
工作电压：400/500V
阻燃等级（据 UL94）：VO
防护等级：IP65
接线形式：螺钉压接
弹片压接
冷压针压接
电缆人口可选螺纹：
M25, PG16, PG21
Rated current: 16A
Rated voltage: 400/500V
Flammability acc. to UL94: VO
Degree of protection acc. to DIN40 050: IP65
Terminal: Screw terminal
Spring terminal
Crimp terminal
Thread: M25, PG16, PG21



UTL-H10B-TS-PG16



UTL-H10B-TG-PG16



UTL-H10B-TS-PG16



UTL-H10B-TG-PG16



UTL-H10B-AG



UTL-H10B-AG



UTL-H10B-SGR



UTL-H10B-SGR

UTL-HDC-HE-010-1
侧面进线 /Side entry

UTL-HDC-HE-010-2
正面进线 /Top entry

UTL-HDC-HE-010-3
侧面进线 /Side entry

UTL-HDC-HE-010-4
正面进线 /Top entry



UTL-H10B-TS-RO



UTL-H10B-TG-RO



UTL-H10B-TSB-PG16



UTL-H10B-TGB-PG16



UTL-H10B-AG-LB



UTL-H10B-AG-LB



UTL-H10B-AD-BO



UTL-H10B-SDR-BO

UTL-HDC-HE-010-1D
侧面进线 /Side entry

UTL-HDC-HE-010-2D
正面进线 /Top entry

UTL-HDC-HE-010-1B
侧面进线 /Side entry

UTL-HDC-HE-010-4B
正面进线 /Top entry



配套外壳 Suit hood/housing

UTL-H10B 上壳 UTL-H10B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------

外壳上壳：侧面进线
Hood:Side entry

	PG16 M25	UTL-H10B-TS PG16 M25	
	PG16 M25	UTL-H10B-TS-RO PG16 M25	
	PG21 PG29 M32	高结构 /High construction UTL-H10B-TSH- PG21 PG29 M32	
	PG16 M25	UTL-H10B-TSB PG16 M25	

外壳上壳：顶部进线
Hood:Top entry

	PG16 M25	UTL-H10B-TG PG16 M25	
	PG21 PG29 M25 M32	高结构 /High construction UTL-H10B-TGH PG21 PG29 M25 M32	
	PG21 PG29 M25 M32	高结构 /High construction UTL-H10B-TGH-RO PG21 PG29 M25 M32	
	PG16 M25	UTL-H10B-TSB PG16 M25	

UTL-H10B 上壳 / 底座螺纹 UTL-H10B hood/housing thread	型号 Type	图纸 Drawing
--	------------	---------------

外壳上壳：顶部进线
Hood:Top entry

	PG16 PG21 M25	UTL-H10B-TG- PG16 PG21 M25	
	PG16 M25	UTL-H10B- TGB-PG16 M25	

外壳底座：开孔安装
Bulkhead:mounted

	UTL-H10B-AG	
	UTL-H10B-AG-LB	
	带保护盖 With protection covers UTL-H10B-AD-BO	

外壳底座：表面安装
Surface mounted:Side entry

	UTL-H10B-SGR-BO- PG16 M25	
	带保护盖 With protection covers UTL-H10B-SGR-BO PG16 M25	



UTL-HE 系列 16 回路接插件套件（带双扣） UTL-HE series 16 Poles of connector (With 2 levers)

UTL-HE-016-M	UTL-HE-016-F	UTL-HE-016 有普通金属单扣和塑料保护盖 UTL-HE-016 有普通金属双扣和塑料保护盖

工作电流：16A
工作电压：400/500V
阻燃等级（据 UL94）：VO
防护等级：IP65
接线形式：螺钉压接
弹片压接
冷压针压接
电缆入口可选螺纹：
M25,PG21,PG29,M32
Rated current: 16A
Rated voltage: 400/500V
Flammabilityacc.to UL94:VO
Degree of protection acc. to
DIN40 050:IP65
Terminal: Screwterminal
Spring terminal
Crimp terminal
Thread:M25 , PG21 ,
PG29 , M32


UTL-H16B-TS-PG21	UTL-H16B-TG-PG21	UTL-H16B-TS-PG21	UTL-H16B-TG-PG21
UTL-H16B-AG	UTL-H16B-AG	UTL-H16B-SGR	UTL-H16B-SGR
UTL-HDC-HE-016-1	UTL-HDC-HE-016-2	UTL-HDC-HE-016-3	UTL-HDC-HE-016-4
侧面进线 /Side entry	正面进线 /Top entry	侧面进线 /Side entry	正面进线 /Top entry
UTL-H16B-TS-RO	UTL-H16B-TG-RO	UTL-H16B-TSB-PG21	UTL-H16B-TGB-PG21
UTL-H16B-AG-LB	UTL-H16B-SGR-LB	UTL-H16B-AD-BO	UTL-H16B-SDR-BO
UTL-HDC-HE-016-1D	UTL-HDC-HE-016-4D	UTL-HDC-HE-016-1B	UTL-HDC-HE-016-4B
侧面进线 /Side entry	正面进线 /Top entry	侧面进线 /Side entry	正面进线 /Top entry




配套外壳 Suit hood/housing

UTL-H16B 上壳 UTL-H16B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------


外壳上壳：侧面进线
Hood:Side entry



侧面带双扣上壳
Side entry housing with 2 levers




外壳上壳：顶部进线
Hood:Top entry




UTL-H16B 上壳 / 底座 UTL-H16B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
---	--------------	------------	---------------


外壳上壳：顶部进线
Hood:Top entry




侧面带双扣上壳
Side entry housing with 2 levers




外壳底座：开孔安装
Bulkhead:mounted




外壳底座：表面安装
Surface mounted:Side entry




4 耳带盖底座
Bulkhead mounted with 2 bolts




UTL-HE 系列 24 回路接插件套件 (带双扣) UTL-HE series 24 Poles of connector (With 2 levers)



工作电流：16A
工作电压：400/500V
阻燃等级 (据 UL94): VO
防护等级：IP65
接线形式：螺钉压接
弹片压接
冷压针压接
电缆入口可选螺纹：
PG21,PG29,M32
Rated current: 16A
Rated voltage: 400/500V
Flammabilityacc.to UL94:VO
Degree of protection acc. to
DIN40 050:IP65
Terminal: Screwterminal
Spring terminal
Crimp terminal
Thread:PG121 , PG29 , M32



UTL-H24B-TS-PG21	UTL-H24B-TG-PG21	UTL-H24B-TSH-PG29	UTL-H24B-TG-PG21
UTL-H24B-AG	UTL-H24B-AG	UTL-H24B-SGR	UTL-H24B-SGR
UTL-HDC-HE-024-1	UTL-HDC-HE-024-2	UTL-HDC-HE-024-3	UTL-HDC-HE-024-4
侧面进线 /Side entry	正面进线 /Top entry	侧面进线 /Side entry	正面进线 /Top entry





UTL-H24B-AD-LB	UTL-H24B-SGR-LB	UTL-H24B-AD-LB	UTL-H24B-SDR-LB
UTL-HDC-HE-024-1DB	UTL-HDC-HE-024-4D	UTL-HDC-HE-024-2B	UTL-HDC-HE-024-4DB
侧面进线 /Side entry	正面进线 /Top entry	正面进线 /Top entry	正面进线 /Top entry






配套外壳 Suit hood/housing

UTL-H24B 上壳 UTL-H24B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------

外壳上壳：侧面进线
Hood:Side entry



外壳上壳：顶部进线
Hood:Top entry




UTL-H24B 上壳 / 底座 UTL-H24B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
---	--------------	------------	---------------


外壳上壳：顶部进线
Hood:Top entry





外壳底座：开孔安装
Bulkhead:mounted



外壳底座：表面安装
Surface mounted:Side entry





4 耳带盖底座
Bulkhead mounted with 2 bolts





配套外壳 Suit hood/housing

UTL-H24B 上壳 UTL-H24B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------

外壳上壳：侧面进线
Hood:Side entry








外壳上壳：顶部进线
Hood:Top entry



UTL-H24B 上壳 UTL-H24B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------





外壳上壳：顶部进线
Hood:Top entry



UTL-HE-016-M(1~16)
UTL-HE-016-M(17~32)

UTL-HE-016-F(1~16)
UTL-HE-016-F(17~32)


UTL-HE-32B 底座锁扣有普通金属单扣和塑料保护盖
UTL-HE-32B 底座锁扣有普通金属双扣

			
UTL-H32B-TS-PG29	UTL-H32B-TG-PG29	UTL-H32B-TS-RO	UTL-H32B-TG-RO
			
UTL-H32B-AG	UTL-H32B-AG	UTL-H32B-AG-LB	UTL-H32B-AD-LB
UTL-HDC-HE-032-1	UTL-HDC-HE-032-2	UTL-HDC-HE-032-1D	UTL-HDC-HE-032-2DB
侧面进线 /Side entry	正面进线 /Top entry	侧面进线 /Side entry	正面进线 /Top entry
			
UTL-H32B-TS-PG29	UTL-H32B-TG-PG29	UTL-H32B-TS-RO	UTL-H32B-TG-RO
			
UTL-H24B-AD-LB	UTL-H24B-SGR-LB	UTL-H24B-AD-LB	UTL-H24B-SDR-LB
UTL-HDC-HE-032-3	UTL-HDC-HE-032-4	UTL-HDC-HE-032-3D	UTL-HDC-HE-032-4DB
侧面进线 /Side entry	正面进线 /Top entry	侧面进线 /Side entry	正面进线 /Top entry

UTL-H32B 上壳 / 底座 UTL-H32B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing	UTL-H32B 底座 UTL-H32B housing	螺纹 Thread	型号 Type	图纸 Drawing
外壳上壳：侧面进线 Hood:Side entry				外壳底座：开孔安装 Bulkhead:mounted			
	PG29 M32	UTL-H32B-TS- PG29 M32				UTL-H32B-AG-LB	
	PG29 M32	UTL-H32B-TS-RO- PG29 M32				UTL-H32B-AD-LB	
外壳上壳：顶部进线 Hood:Top entry				外壳底座：表面安装 Surface mounted:Side entry			
	PG29 M32	UTL-H32B-TG- PG29 M32			PG29 M32	UTL-H32B-SGR- PG29 M32	
	PG29 M32	UTL-H32B-TG-RO PG29 M32			PG29 M32	UTL-H32B-SGR-LB- PG29 M32	
外壳底座：开孔安装 Bulkhead:mounted							
		UTL-H32B-AG			PG29 M32	UTL-H32B-SDR-LB PG29 M32	




UTL-HE 系列 48 回路接插件套件 UTL-HE series 48 Poles of connector



工作电流：16A
工作电压：400/500V
阻燃等级 (据 UL94): VO
防护等级：IP65
接线形式：螺钉压接
弹片压接
冷压针压接
电缆人口可选螺纹：
PG29,PG36,M40

Rated current: 16A
Rated voltage: 400/500V
Flammabilityacc.to UL94:VO
Degree of protection acc. to
DIN40 050:IP65
Terminal: Screwterminal
Spring terminal
Crimp terminal
Thread:PG29 , PG36 , M40



配套外壳 Suit hood/housing

UTL-H48B 上壳 / 底座 UTL-H48B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
外壳上壳：侧面进线 Hood:Side entry	PG29 PG36 M40	UTL-H48B-TS-RO-PG29 UTL-H48B-TS-RO-PG36 UTL-H48B-TS-RO-M40	
外壳上壳：顶部进线 Hood:Top entry	PG29 PG36 M40	UTL-H48B-TG-RO-PG29 UTL-H48B-TG-RO-PG36 UTL-H48B-TG-RO-M40	
外壳底座：开孔安装 Bulkhead:mounted		UTL-H48B-AG-LB	
		UTL-H48B-AD-LB-	
A 外壳底座：表面安装 Surface mounted:Side entry	PG29 PG36 M40	UTL-H48B-SGR-LB-PG29 UTL-H48B-SGR-LB-PG36 UTL-H48B-SGR-LB-M40	
	PG29 PG36 M40	UTL-H48B-SDR-LB-PG29 UTL-H48B-SDR-LB-PG36 UTL-H48B-SDR-LB-M40	




UTL-HEE 系列 18 回路接插件套件 UTL-HEE series 18 Poles of connector



UTL-HEE-018-M



UTL-HEE-018-F





UTL-H10B-018 底座锁扣有普通金属单扣和塑料保护盖
UTL-H10B-018 底座锁扣有普通金属双扣和塑料保护盖
UTL-HEE 系列芯件均为冷压针 (HEE) 压接型, 冷压针需另外订购



配套外壳 Suit hood/housing

UTL-H16B 上壳 UTL-H16B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------

外壳上壳: 侧面进线
Hood: Side entry








外壳上壳: 顶部进线
Hood: Top entry



UTL-H16B 上壳/底座 UTL-H16B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
---	--------------	------------	---------------

外壳上壳: 顶部进线
Hood: Top entry




UTL-HEE 系列 32 回路接插件套件 UTL-HEE series 32 Poles of connector



UTL-HEE-032-M



UTL-HEE-032-F





UTL-H16B 底座锁扣有普通金属单扣和塑料保护盖
UTL-H16B 底座锁扣有普通金属双扣和塑料保护盖
UTL-HEE 系列芯件均为冷压针 (HEE) 压接型, 冷压针需另外订购





配套外壳 Suit hood/housing

UTL-H16B 上壳 UTL-H16B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------

外壳上壳: 侧面进线
Hood: Side entry






侧面带双扣上壳
Side entry housing with 2 levers







UTL-H16B 上壳/底座 UTL-H16B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
---	--------------	------------	---------------

外壳上壳: 顶部进线
Hood: Top entry




外壳底座: 表面安装
Surface mounted: Side entry





UTL-HEE 系列 46 回路接插件套件 UTL-HEE series 46 Poles of connector




配套外壳 Suit hood/housing

UTL-H24B 上壳 UTL-H24B hood	螺纹 Thread	型号 Type	图纸 Drawing	UTL-H24B 上壳 / 底座螺纹 UTL-H24B hood/housing thread	型号 Type	图纸 Drawing
外壳上壳：侧面进线 Hood:Side entry				外壳上壳：顶部进线 Hood:Top entry		
	PG21 M25 M32	UTL-H24B-TS- PG21 M25 M32			PG21 PG29 M32	
	PG29	高结构 /High construction UTL-H24B-TSH- PG29		外壳底座：开孔安装 Bulkhead:mounted		
	PG21 M25 M32	UTL-H24B-TS-RO- PG21 M25 M32			UTL-H24B-AG	
外壳上壳：顶部进线 Hood:Top entry				外壳底座：表面安装 Surface mounted:Side entry		
	PG21 M25 M32	UTL-H24B-TS-RO- PG21 M25 M32			PG21 PG29 M32	
	PG29	高结构 /High construction UTL-H24B-TGH- PG29			PG21 PG29 M32	
	2*PG21	UTL-H24B-TGH-RO- 2*PG21		4 耳带盖底座 Bulkhead mounted with 2 bolts		
					UTL-H24B-AD-LB	



UTL-HEE 系列 64 回路接插件套件 UTL-HEE series 64 Poles of connector




配套外壳 Suit hood/housing

UTL-H32B 上壳 UTL-H32B hood	螺纹 Thread	型号 Type	图纸 Drawing	UTL-H32B 上壳 / 底座 UTL-H32B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
外壳上壳：侧面进线 Hood:Side entry				外壳底座：开孔安装 Bulkhead:mounted			
	PG29 M32	UTL-H32B-TS- PG29 M32				UTL-H32B-AG	
	PG29 M32	UTL-H32B-TS-RO- PG29 M32				UTL-H32B-AG-LB	
外壳上壳：顶部进线 Hood:Top entry				外壳底座：开孔安装 Bulkhead:mounted			
	PG29 M32	UTL-H32B-TG- PG29 M32			PG29 M32	UTL-H32B-SGR- PG29 M32	
	PG29 M32	UTL-H32B-TG-RO- PG29 M32			PG29 M32	UTL-H32B-SGR-LB- PG29 M32	



UTL-HEE 系列 92 回路接插件套件 UTL-HEE series 92 Poles of connector




配套外壳 Suit hood/housing

UTL-H48B 上壳 / 底座 UTL-H48B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
外壳上壳：侧面进线 Hood:Side entry	PG29 PG36 M40	UTL-H48B-TS-RO-PG29 UTL-H48B-TS-RO-PG36 UTL-H48B-TS-RO-M40	
外壳上壳：顶部进线 Hood:Top entry	PG29 PG36 M40	UTL-H48B-TG-RO-PG29 UTL-H48B-TG-RO-PG36 UTL-H48B-TG-RO-M40	
外壳底座：开孔安装 Bulkhead:mounted		UTL-H48B-AG-LB	
		UTL-H48B-AD-LB	
外壳底座：表面安装 Surface mounted:Side entry	PG29 PG36 M40	UTL-H48B-SGR-LB-PG29 UTL-H48B-SGR-LB-PG36 UTL-H48B-SGR-LB-M40	
	PG29 PG36 M40	UTL-H48B-SDR-LB-PG29 UTL-H48B-SDR-LB-PG36 UTL-H48B-SDR-LB-M40	



UTL-HDD 系列 24 回路接插件套件 UTL-HDD series 24 Poles of connector




配套外壳 Suit hood/housing

UTL-H6B 上壳 UTL-H6B hood	螺纹 Thread	型号 Type	图纸 Drawing	UTL-H6B 底座 UTL-H6B housing	螺纹 Thread	型号 Type	图纸 Drawing
外壳上壳：侧面进线 Hood:Side entry	PG13.5 PG16 M20	UTL-H6B-TS-RO- PG13.5 PG16 M20		外壳底座：开孔安装 Bulkhead:mounted			
	PG13.5 PG16 M20	UTL-H6B-TS-RO- PG13.5 PG16 M20					
	高结构 /High construction PG21 PG29	UTL-H6B-TSH-RO- PG21 PG29		带保护盖 Without protection covers UTL-H6B-AD-LB			
外壳上壳：顶部进线 Hood:Top entry	PG13.5 PG16 M20	UTL-H6B-TG-RO- PG13.5 PG16 M20		外壳底座：表面安装 Surface mounted:Side entry	PG13.5 PG16 M20	UTL-H6B-SGR-LB- PG13.5 PG16 M20	
	高结构 /High construction PG16 PG21	UTL-H6B-TGH-RO- PG16 PG21					
	PG13.5 PG16 M20	UTL-H6B-TG-RO- PG13.5 PG16 M20		带保护盖 Without protection covers PG13.5 PG16 M20	PG13.5 PG16 M20	UTL-H6B-SDR-LB- PG13.5 PG16 M20	



UTL-HDD 系列 42 回路接插件套件 UTL-HDD series 42 Poles of connector




配套外壳 Suit hood/housing

UTL-H32B 上壳 UTL-H32B hood	螺纹 Thread	型号 Type	图纸 Drawing	UTL-H32B 上壳 / 底座螺纹 UTL-H32B hood/housing thread	型号 Type	图纸 Drawing
外壳上壳：侧面进线 Hood:Side entry				外壳上壳：顶部进线 Hood:Top entry		
	PG16 M20 M25	UTL-H10B-TS- PG16 M20 M25			PG16 M25	UTL-H10B-TGR- PG16 M25
	PG21 PG29 M32	高结构 /High construction UTL-H10B-TSH-PG21- PG21 PG29 M32		外壳底座：开孔安装 Bulkhead:mounted		
	PG16 M25	UTL-H10B-TSB- PG16 M25				UTL-H10B-AG
外壳上壳：顶部进线 Hood:Top entry						UTL-H10B-AG-LB
	PG16 M25	UTL-H10B-TG- PG16 M25		带保护盖 Without protection covers UTL-H10B-AD-BO		
	PG21 PG29 M32	高结构 /High construction UTL-H10B-TGH- PG21 PG29 M32		外壳底座：表面安装 Surface mounted:Side entry		
	PG16 PG21	UTL-H10B-TG- PG16 PG21				UTL-H10B-SGR- PG16 M25
				带保护盖 Without protection covers UTL-H10B-SDR-BO		



UTL-HDD 系列 72 回路接插件套件 UTL-HDD series 72 Poles of connector



配套外壳 Suit hood/housing

UTL-H16B 上壳 UTL-H16B hood	螺纹 Thread	型号 Type	图纸 Drawing	UTL-H16B 上壳 / 底座 UTL-H16B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
外壳上壳：侧面进线 Hood:Side entry				外壳上壳：顶部进线 Hood:Top entry			
	PG21 M25 M32	UTL-H16B-TS- PG21 M25 M32			PG29	UTL-H16B-TGH-RO- PG29	
	PG29	高结构 /High construction UTL-H16B-TSH- PG29		顶部带双扣上壳 Top entry housing with 2 levers			
	PG21 M25 M32	H16B-TSB- PG21 M25 M32			PG21 M25 M32	UTL-H16B-TGB- PG21 M25 M32	
侧面带双扣上壳 Side entry housing with 2 levers				外壳底座：开孔安装 Bulkhead:mounted			
	PG21 M25 M32	UTL-H16B-TG- PG21 M25 M32				UTL-H16B-AG M32	
	PG21 M25 M32	UTL-H16B-TG-RO- PG21 M25 M32		带保护盖 Without protection covers UTL-H16B-AD-BO			
				外壳底座：表面安装 Surface mounted:Side entry			
	PG21 M25 M32	UTL-H16B-TG- PG21 M25 M32			PG21 M25	UTL-H16B-SGR- PG21 M25	
	PG21 M25 M32	UTL-H16B-TG- PG21 M25 M32		带保护盖 Without protection covers UTL-H16B-DR-BO	PG21 M25 M32	UTL-H16B-DR-BO- PG21 M25 M32	

UTL-HDD-108-M

UTL-HDD-108-F

UTL-H24B 底座锁扣有普通金属单扣和塑料保护盖
UTL-H24F 底座锁扣有普通金属双扣和塑料保护盖

UTL-H24B 上壳	螺纹	型号	图纸
UTL-H24B hood	Thread	Type	Drawing

PG21 UTL-H24B-TS-
M25 PG21
M32 M25
M32

Technical drawing of the UTL-H24B-TS- connector. The side view shows a length of 120 and a mounting hole spacing of 43. The end view shows a width of 62. The drawing is labeled with 'PG21' and 'M25'.

 **PG29** 高结构 /High construction
UTL-H24B-TSH-PG29

 **PG29** Dimensions: 120, 42, 75.2

PG21 UTL-H24B-TS-R
M25 PG21
M32 M25

PG21	UTL-H24B-TS-RO
M25	PG21
M32	M25
	M32


 高结构 /High construction
 UTL-H24B-TGH-PG29



 2*PG21 UTL-H24B-TGH-RO-
2*PG21
 


UTL-H24B 上壳 / 底座	螺纹	型号	图纸
UTL-H24B hood/housing	Thread	Type	Drawing


 PG21
 PG29
 M32

UTL-H24B-TGHB-
 PG21
 PG29
 M32


 120
 43
 75.9

UTL-H24B-AG

PG21
PG29
M32

UTL-H24B-SG90

MPH

72

67

132

143.5

45

57

PG21 UTL-H24B-SGR
 PG29 PG21
 M32 PG29
 M32

Technical drawing showing the side view of the UTL-H24B-SGR connector. Dimensions include 132 (length), 72 (height), and 45 (mounting hole diameter). Labels PG21, PG29, and M32 are present.

UTL-H24B-AD-LB

UTL-HDD-072-M(1~72)
UTL-HDD-072-M(73~144)

UTL-HDD-072-F(1~72)
UTL-HDD-072-F(73~144)

UTL-H32B 底座锁扣有普通金属单扣和塑料保护盖
UTL-H32B 底座锁扣有普通金属双扣和塑料保护盖

UTL-H32B 上壳 UTL-H32B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------

PG29 UTL-H32B-TS-
M32 PG29
M32

 PG29 UTL-H32B-TS-RO
M32 PG29
M32

 **PG29 M32** UTL-H32B-TG-PG29 M32

 **MPG**

94.5 83 74.5


 PG29 M32 UTL-H32B-TG-RO-
 PG29 M32


 MPG


 94.5 83 74.5

UTL-H32B 底座 UTL-H32 B housing	螺纹 Thread	型号 Type	图纸 Drawing
----------------------------------	--------------	------------	---------------

Technical drawing of the 'L' shaped bracket (Fig. 10). The side view shows a bracket with a horizontal base of 125.2 and a vertical stem of 35. The front view shows a bracket with a horizontal base of 83.6 and a vertical stem of 35.

UTL-H32B-AG-LB



PG29
M32

UTL-H32B-SGR-
PG29
M32




PG29
M32







UTL-H32B-SGR-LB
PG29
M32

Technical drawing of the UTL-H32B-SGR-LB unit. The drawing shows a side view with dimensions 112 and 123, and a top view with dimensions 89, 67, and 86. A hand is shown operating the top handle.


UTL-HDD 系列 216 回路接插件套件 UTL-HDD series 216 Poles of connector




配套外壳 Suit hood/housing

H48B 上壳 / 底座 H48B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
外壳上壳：侧面进线 Hood:Side entry			
	PG29 PG36 M40	UTL-H48B-TS-RO-PG29 UTL-H48B-TS-RO-PG36 UTL-H48B-TS-RO-M40	
外壳上壳：顶部进线 Hood:Top entry			
	PG29 PG36 M40	UTL-H48B-TG-RO-PG29 UTL-H48B-TG-RO-PG36 UTL-H48B-TG-RO-M40	
外壳底座：开孔安装 Bulkhead:mounted			
		UTL-H48B-AG-LB	
		UTL-H48B-AD-LB	
外壳底座：表面安装 Surface mounted:Side entry			
	PG29 PG36 M40	UTL-H48B-SGR-LB-PG29 UTL-H48B-SGR-LB-PG36 UTL-H48B-SGR-LB-M40	
	PG29 PG36 M40	UTL-H48B-SDR-LB-PG29 UTL-H48B-SDR-LB-PG36 UTL-H48B-SDR-LB-M40	

UTL-HSB-006 系列 UTL-HSB-006series



工作电流：35A
 工作电压：400/690V
 阻燃等级（据 UL94）：VO
 防护等级：IP65
 接线形式：弹片压接
 弹片压接
 冷压针压接
 电缆人口可选螺纹：
 M25,PG21,PG29,M32
 Rated current: 35A
 Rated voltage: 400/690V
 Flammability acc. to UL94: VO
 Degree of protection acc. to
 DIN40 050: IP65
 Terminal: Screwterminal
 Spring terminal
 Crimp terminal
 Thread: M25 , PG121 ,
 PG29 , M32







配套外壳 Suit hood/housing

UTL-H24B 上壳 UTL-H24B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------


外壳上壳：侧面进线
Hood:Side entry



侧面带双扣上壳
Side entry housing with 2 levers




外壳上壳：顶部进线
Hood:Top entry




UTL-H24B 上壳 / 底座 UTL-H24B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
---	--------------	------------	---------------


外壳上壳：顶部进线
Hood:Top entry




顶部带双扣上壳
Top entry housing with 2 levers




外壳底座：开孔安装
Bulkhead:mounted




外壳底座：表面安装
Surface mounted:Side entry




4 耳带盖底座
Bulkhead mounted with 2 bolts




UTL-HSB-012 系列 UTL-HSB-012 series



工作电流：35A
工作电压：400/690V
阻燃等级 (据 UL94): VO
防护等级：IP65
接线形式：螺钉压接
弹片压接
冷压针压接
电缆人口可选螺纹：
M25,PG21,PG29,M32
Rated current: 35A
Rated voltage: 400/690V
Flammabilityacc.to UL94:VO
Degree of protection acc. to
DIN40 050:IP65
Terminal: Screwterminal
Spring terminal
Crimp terminal
Thread:M25 , PG21 ,
PG29 , M32



UTL-HSB-012-1	UTL-HSB-012-2	UTL-HSB-012-1D	UTL-HSB-012-2D
侧面进线 /Side entry	正面进线 /Top entry	侧面进线 /Side entry	正面进线 /Top entry








配套外壳 Suit hood/housing

UTL-H32B 上壳 UTL-H32B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------

外壳上壳：侧面进线
Hood:Side entry





外壳上壳：顶部进线
Hood:Top entry





UTL-H32B 底座 UTL-H32B housing	螺纹 Thread	型号 Type	图纸 Drawing
---------------------------------	--------------	------------	---------------


外壳底座：开孔安装
Bulkhead:mounted



外壳底座：开孔安装
Bulkhead:mounted



UTL-HK 系列 UTL-HK series




UTL-HK-004/2-M



UTL-HK-004/2-F

UTL-H16B 底座锁扣有普通金属单扣和塑料保护盖
UTL-H16B 底座锁扣有普通金属双扣和塑料保护盖

工作电流：80A
工作电压：400/690V
阻燃等级 (据 UL94): VO
防护等级：IP65
接线形式：螺钉压接
弹片压接
电缆入口可选螺纹：
M25,PG21,PG29,M32
Rated current: 80A
Rated voltage: 400/690V
Flammabilityacc. to UL94:VO
Degree of protection acc. to DIN40 050:IP65
Terminal: Screwterminal
Spring terminal
Thread:M25 , PG21 , PG29 , M32



UTL-H16B-AG	UTL-H16B-AG	UTL-H16B-SGR	UTL-H16B-SGR
UTL-HDC-HK-004-1	UTL-HDC-HK-004-2	UTL-HDC-HK-004-3	UTL-HDC-HK-004-4
侧面进线 /Side entry	正面进线 /Top entry	侧面进线 /Side entry	正面进线 /Top entry







配套外壳 Suit hood/housing

UTL-H16B 上壳 UTL-H16B hood	螺纹 Thread	型号 Type	图纸 Drawing
------------------------------	--------------	------------	---------------

外壳上壳：侧面进线
Hood:Side entry



侧面带双扣上壳
Side entry housing with 2 levers




外壳上壳：顶部进线
Hood:Top entry



UTL-H16B 上壳 / 底座 UTL-H16B hood/housing	螺纹 Thread	型号 Type	图纸 Drawing
---	--------------	------------	---------------


外壳上壳：顶部进线
Hood:Top entry




顶部带双扣上壳
Top entry housing with 2 levers




外壳底座：开孔安装
Bulkhead:mounted



外壳底座：表面安装
Surface mounted:Side entry




4 耳带盖底座
Bulkhead mounted with 2 bolts




16A 冷压接插针 16A Crimo contacts

材料：铜
Material: copper
接触电阻 /Contact resistance : $\leq 1\text{m}\Omega$
接线形式：冷压工具压接
Termianl : cripe connection

公接插针 /Mate crimp contacts



母接插针 /Female crimp contacts




线径 Wire gauge	接线长度 Stripping length	镀银冷压针型号 Contacts , Silver-plated	镀金冷压针型号 Contacts , Gold-plated
0.5mm ²	AWG 20 7.5mm	CEM-0.5	DEM-0.5
0.75mm ²	AWG 18 7.5mm	CEM-0.75	DEM-0.75
1.0mm ²	AWG 18 7.5mm	CEM-1.0	DEM-1.0
1.5mm ²	AWG 16 7.5mm	CEM-1.5	DEM-1.5
2.5mm ²	AWG 14 7.5mm	CEM-2.5	DEM-2.5
4.0mm ²	AWG 12 7.5mm	CEM-4.0	DEM-4.0

线径 Wire gauge	接线长度 Stripping length	镀银冷压针型号 Contacts , Silver-plated	镀金冷压针型号 Contacts , Gold-plated
0.5mm ²	AWG 20 7.5mm	CEM-0.5	DEM-0.5
0.75mm ²	AWG 18 7.5mm	CEM-0.75	DEM-0.75
1.0mm ²	AWG 18 7.5mm	CEM-1.0	DEM-1.0
1.5mm ²	AWG 16 7.5mm	CEM-1.5	DEM-1.5
2.5mm ²	AWG 14 7.5mm	CEM-2.5	DEM-2.5
4.0mm ²	AWG 12 7.5mm	CEM-4.0	DEM-4.0


10A 冷压接插针 10A Crimo contacts

材料：铜
Material: copper
接触电阻 /Contact resistance : $\leq 3\text{m}\Omega$
接线形式：冷压工具压接
Termianl : cripe connection

公接插针 /Mate crimp contacts



母接插针 /Female crimp contacts




线径 Wire gauge	接线长度 Stripping length	镀银冷压针型号 Contacts , Silver-plated	镀金冷压针型号 Contacts , Gold-plated
0.5mm ²	AWG 20 8.0mm	DDM-0.5	DDM-0.5
0.75mm ²	AWG 18 8.0mm	DDM-0.75	DDM-0.75
1.0mm ²	AWG 18 8.0mm	DDM-1.0	DDM-1.0
1.5mm ²	AWG 16 8.0mm	DDM-1.5	DDM-1.5
2.5mm ²	AWG 14 8.0mm	DDM-2.5	DDM-2.5

线径 Wire gauge	接线长度 Stripping length	镀银冷压针型号 Contacts , Silver-plated	镀金冷压针型号 Contacts , Gold-plated
0.5mm ²	AWG 20 8.0mm	DDF-0.5	DDF-0.5
0.75mm ²	AWG 18 8.0mm	DDF-0.75	DDF-0.75
1.0mm ²	AWG 18 8.0mm	DDF-1.0	DDF-1.0
1.5mm ²	AWG 16 8.0mm	DDF-1.5	DDF-1.5
2.5mm ²	AWG 14 8.0mm	DDF-2.5	DDF-2.5


40A 冷压接插针 40A Crimo contacts

材料：铜
Material: copper
接触电阻 /Contact resistance : $\leq 4\text{m}\Omega$
接线形式：冷压工具压接
Termianl : cripe connection

公接插针 /Mate crimp contacts



母接插针 /Female crimp contacts



线径 Wire gauge	接线长度 Stripping length	镀银冷压针型号 Contacts , Silver-plated	镀金冷压针型号 Contacts , Gold-plated
1.75mm ²	AWG 16 8.0mm	CEM-1.5	DMM-1.5
2.25mm ²	AWG 14 8.0mm	CEM-2.5	DMM-2.5
2.85mm ²	AWG 12 8.0mm	CEM-4.0	DMM-4.0
3.50mm ²	AWG 10 8.0mm	CEM-6.0	DMM-6.0

线径 Wire gauge	接线长度 Stripping length	镀银冷压针型号 Contacts , Silver-plated	镀金冷压针型号 Contacts , Gold-plated
1.75mm ²	AWG 16 8.0mm	CMF-1.5	DMF-1.5
2.25mm ²	AWG 14 8.0mm	CMF-2.5	DMF-2.5
2.85mm ²	AWG 12 8.0mm	CMF-4.0	DMF-4.0
3.50mm ²	AWG 10 8.0mm	CMF-6.0	DMF-6.0

冷压退针工具 Crimping tool and removal tool

压线钳：压接范围 0.5~4.0mm²
Crimping tool: crimping wire range 0.5~4.0mm²
适用压接 HD/HDD , HEE 冷压针
For HD/HDD , HEE Crimp contacts



CRIMPBOX-0.5/4
压线钳 Crimping tool




REMOV-HEE
UTL-HEE 系列冷压针退针器
UTL-HEE series crimp contact removal tool



REMOV-HED
UTL-HD/HDD 系列冷压针退针器
UTL-HD/HDD series crimp contact removal tool


Coding pins
编码销（导向销）

编码销




订货号：CODE-M3

适用于可安装一个插体或框架的外壳




模块型编码销



订货号：MCODE-M3


适用于可安装两个插体或框架的外壳



● 编码销
○ 正常螺丝




M- 公插体
F- 母插体

导向孔




订货号：GBUSH-M3

适用于可安装一个插体或框架的外壳




模块型导向孔




订货号：MGBUSH-M3

导向销




订货号：GPIN-M3

适用于可安装两个插体或框架的外壳




模块型导向销



订货号：MGPIN-M3

编号销



订货号：CODE-E

- ①使用此编码销，可避免相同连接器的误插，
- ②适用于 UTL-HEC，UTL-HEE，UTL-HQ5/0，UTL-HM-006，UTL-HM-008
- ③使用编码销时，公插对应孔不能装插针

编号销



订货号：CODE-D

- ①使用此编码销，可避免相同连接器的误插，
- ②适用于 UTL-HD，UTL-HDD，UTL-HMD-012，UTL-HMDD-014，UTL-HQ7/0，UTL-HQ12/0
- ③使用编码销时，公插对应孔不能装插针



Insert Series
接插体

UTL-HA 系列 /UTL-HA series


额定电流 /Rated current：10A
额定电压 /Reted voltage：230/250V
压接形式：螺钉压接
Technical：Screw termianl



公插体 / 母插体 (M/F)	UTL-HA-003-M	UTL-HA-003-F	UTL-HA-004-M	UTL-HA-004-F
导线额定截面 /Wire gauge	0.5-2.5mm²		0.5-2.5mm²	

UTL-HA 系列 /UTL-HA series

额定电流 /Rated current：10A
额定电压 /Reted voltage：230/250V
压接形式：螺钉压接
Technical：Screw termianl



公插体 / 母插体 (M/F)	UTL-HA-010-M	UTL-HA-010-F	UTL-HA-016-M	UTL-HA-016-F
导线额定截面 /Wire gauge	0.5-2.5mm²		0.5-2.5mm²	

UTL-HE 系列 /UTL-HE series

额定电流 /Rated current：10A
额定电压 /Reted voltage：230/250V
压接形式：螺钉压接
Technical：Screw termianl



公插体 / 母插体 (M/F)	UTL-HE-006-M	UTL-HE-006-F	UTL-HE-010-M	UTL-HE-010-F	UTL-HE-016-M	UTL-HE-016-F
导线额定截面 /Wire gauge	0.5-4.0mm²		0.5-4.0mm²		0.5-4.0mm²	

UTL-HE 系列 /UTL-HE series

额定电流 /Rated current：10A
额定电压 /Reted voltage：230/250V
压接形式：螺钉压接
Technical：Screw termianl



公插体 / 母插体 (M/F)	UTL-HE-024-M	UTL-HE-024-F	UTL-HE-032-M	UTL-HE-032-F	UTL-HE-048-M	UTL-HE-048-F
导线额定截面 /Wire gauge	0.5-4.0mm²		0.5-4.0mm²		0.5-4.0mm²	

Insert Series
接插体

UTL-HEE 系列 /UTL-HEE series

额定电流 /Rated current : 10A
额定电压 /Reted voltage : 230/250V
压接形式：螺钉压接
Technical : Screw termianl



公插体 / 母插体 (M/F)	UTL-HEE-032-M UTL-HEE-032-M	UTL-HEE-046-M UTL-HEE-046-M
导线额定截面 /Wire gauge	0.5-4.0mm²	0.5-4.0mm²

额定电流 /Rated current : 10A
额定电压 /Reted voltage : 230/250V
压接形式：螺钉压接
Technical : Screw termianl



公插体 / 母插体 (M/F)	UTL-HDD-024-M UTL-HDD-024-F	UTL-HDD-072-M UTL-HDD-072-F	UTL-HDD-108-M UTL-HDD-108-F
导线额定截面 /Wire gauge	0.5-2.5mm²	0.5-2.5mm²	0.5-2.5mm²

UTL-HE 系列 /UTL-HE series

额定电流 /Rated current : 10A
额定电压 /Reted voltage : 230/250V
压接形式：螺钉压接
Technical : Screw termianl



公插体 / 母插体 (M/F)	UTL-HSB-006-M UTL-HSB-006-F	UTL-HK-004/2-M UTL-HK-004/2-F	UTL-HK-006/12-M UTL-HK-006/12-F
导线额定截面 /Wire gauge	0.5-4.0mm²	0.5-4.0mm²	0.5-4.0mm²

UTL-HK 系列 /UTL-HK series

额定电流 /Rated current : 10A
额定电压 /Reted voltage : 230/250V
压接形式：螺钉压接
Technical : Screw termianl



	UTL-HK-6/6-M UTL-HK-6/6-F	UTL-HK-004/8-M UTL-HK-004/8-F
导线额定截面 /Wire gauge	0.5-4.0mm²	0.5-4.0mm²




Complete Set Combination
成套组合

配套外壳 Suit hood/housing

工业重载连接器 500V Max16A




UTL-HDC-HA-004-1




工业重载连接器 500V Max16A




UTL-HDC-HA-010-4




UTL-HDC-HE-006-1




UTL-HDC-HE-006-4




UTL-HDC-HE-010-3D




UTL-HDC-HE-006-4




UTL-HDC-HE-010-2D




UTL-HDC-HE-010-1



UTL-HDC-HE-016-5




UTL-HDC-HE-016-3D







配套外壳 Suit hood/housing




UTL-HDC-HE-016-2




UTL-HDC-HE-010-3





UTL-HDC-HE-016-1




UTL-HDC-HE-024-1D





UTL-HDC-HE-024-4




UTL-HDC-HE-024-5





UTL-HDC-HE-024-1



UTL-HDC-HE-024-3



UTL-HDC-HE-024-4D



UTL-HDC-HE-024-5