

Mounting pads

* = transfer washer: the US-pads convert the TO 5 pin circle to a pitch of 2.54 mm

art. no. MS 184 7 TO 18	art. no. MS 184 35 TO 18	art. no. MS 53 7 TO 5	art. no. US 58 4 TO 5	
material:		polyamide 6, GF reinforced		
temperature range:		-40°C... +205°C		
class of inflammability:		UL 94 V-0 (at thickness ≥3mm), UL 94 V-1		
art. no. MS 923 25 TO 92	art. no. MS 183 25 TO 18	art. no. MS 184 25 TO 18	art. no. MS 183 7 TO 18	art. no. MS 183 35 TO 18
art. no. MS 3518 25 TO 5/TO 18	art. no. MS 3518 35 TO 5/TO 18	art. no. MS 58 5 TO 5-8 p.	art. no. MS 53 25 TO 5	art. no. MS 54 25 TO 5
art. no. MS 34 518 TO 5/TO 18	art. no. MS 58 7 TO 5-8 p.	art. no. MS 53 3 TO 5	art. no. MS 56 15 TO 5-6 p.	art. no. MS 58 15 TO 5-8 p.
art. no. MS 510 15 TO 5-10 p.	art. no. MS 84 4 TO 8	art. no. MS 4016 max. 16 contacts	art. no. US 512 4 TO 5	
material:		polyamide 6, GF reinforced		
temperature range:		permanent up to 100°C		
class of inflammability:		UL 94 V-0		