

A

Extruded heatsinks for PCB mounting

- compact PCB heatsinks
- especially suitable for vertical PCB mounting in housings, racks etc.
- easy solder fixing
- special versions on customer's request
- **L** = solderable pin

B

C

D

E

F

G

H













I

K

L

M

N

	SK 454 20 1 x M 3 L			SK 454 40 2 x M 3 L			SK 454 60 3 x M 3 L		
									
art. no.	l [mm]	R_{th} [K/W]							
SK 454 20 1 x M3 L	20	10.1	SOT 32/ TO 220						
SK 454 40 2 x M3 L	40	8.8							
SK 454 60 3 x M3 L	60	7.5							
	SK 448 20 1 x M 3 L			SK 448 40 2 x M 3 L			SK 448 60 3 x M 3 L		
									
art. no.	l [mm]	R_{th} [K/W]							
SK 448 20 1 x M3 L	20	11.8	TO 218/ TO 220/ TO 247/ TO 248/ TO 3 P						
SK 448 40 2 x M3 L	40	9.8							
SK 448 60 3 x M3 L	60	7.1							
	SK 400 20 1 x M 3 L			SK 400 40 2 x M 3 L			SK 400 60 3 x M 3 L		
									
art. no.	l [mm]	R_{th} [K/W]							
SK 400 20 1 x M3 L	20	11.6	TO 218/ TO 220/ TO 247/ TO 248/ TO 3 P						
SK 400 40 2 x M3 L	40	8.2							
SK 400 60 3 x M3 L	60	7.2							
	SK 456 20 1 x M 3 L			SK 456 40 2 x M 3 L			SK 456 60 3 x M 3 L		
									
art. no.	l [mm]	R_{th} [K/W]							
SK 456 20 1 x M3 L	20	13.0	TO 218/ TO 220/ TO 247/ TO 248/ TO 3 P						
SK 456 40 2 x M3 L	40	10.5							
SK 456 60 3 x M3 L	60	8.5							
surface:		black anodised							

