

M8 Quick Search Table	Available Coding	A-coding		A-coding		B-coding		A-coding			
	Rated Current	3A		3A		3A		1.5A			
	Voltage	50V(A/C), 60V(D/C)		50V(A/C), 60V(D/C)		30V(A/C), 30V(D/C)		30V(A/C), 30V(D/C)			
	Wire Gauge / size	24AWG / 0.25mm <sup>2</sup>		24AWG / 0.25mm <sup>2</sup>		24AWG / 0.25mm <sup>2</sup>		26AWG / 0.14mm <sup>2</sup>			
	Pin layout										
M8 cables & connectors		03 Pins		04 Pins		05 Pins		06 Pins		08 Pins	
<b>Molded Cable</b>											
	Male Molded Cable Straight	23	-	23	-	23	-	23	-	23	-
	Male Molded Cable Straight Shielded	26	-	26	-	26	-	26	-	26	-
	Male Molded Cable Straight Snap-in	28	-	28	-	-	-	-	-	-	-
	Female Molded Cable Straight	-	24	-	24	-	24	-	24	-	24
	Female Molded Cable Straight Plastic	-	25	-	25	-	25	-	25	-	25
	Female Molded Cable Straight Shielded	-	27	-	27	-	27	-	27	-	27
	Female Molded Cable Straight Snap-in	-	29	-	29	-	-	-	-	-	-
	Male Molded Cable Angled	30	-	30	-	30	-	30	-	30	-
	Male Molded Cable Angled Shielded	33	-	33	-	33	-	33	-	33	-
	Male Molded Cable Angled Snap-in	35	-	35	-	-	-	-	-	-	-
	Female Molded Cable Angled	-	31	-	31	-	31	-	31	-	31
	Female Molded Cable Angled Plastic	-	32	-	32	-	32	-	32	-	32
	Female Molded Cable Angled Shielded	-	34	-	34	-	34	-	34	-	34
	Female Molded Cable Angled Snap-in	-	36	-	36	-	-	-	-	-	-
Female Molded Cable Angled with LED	-	37	-	37	-	-	-	-	-	-	
<b>Assembly Type</b>											
	Male Field Wirable Assembly Straight Solder	38	-	38	-	38	-	38	-	38	-
	Female Field Wirable Assembly Straight Solder	-	39	-	39	-	39	-	39	-	39
	Male Field Wirable Assembly Straight Screw Joint Shielded	40	-	40	-	40	-	40	-	40	-
	Female Field Wirable Assembly Straight Screw Joint Shielded	-	41	-	41	-	41	-	41	-	41
<b>Panel Mount Type</b>											
	Male Panel Mount Solder Front fastened	42	-	42	-	42	-	42	-	42	-
	Male Panel Mount Solder Rear fastened	44	-	44	-	44	-	44	-	44	-
	Male Panel Mount Solder with LED	-	-	48	-	-	-	-	-	-	-
	Female Panel Mount Solder Front fastened	46	-	46	-	-	-	-	-	-	-
	Female Panel Mount Solder Rear fastened	47	-	47	-	-	-	-	-	-	-
	Male Panel Mount PCB Type Front fastened	49/51	-	49/51	-	49	-	-	-	-	-
	Male Panel Mount Angled PCB Type Front fastened Shielded	53	-	53	-	53	-	-	-	-	-
	Female Panel Mount PCB Type Front fastened	50	-	50	-	50	-	50	-	50	-
	Female Panel Mount Angled PCB Type Front fastened Shielded	54	-	54	-	54	-	-	-	-	-
Male to Female Panel Mount	52	52	52	52	52	52	-	-	-	-	
<b>Splitter Connector</b>											
	Y-Splitter Male-2 Female	55	55	55	55	55	55	-	-	-	-
	L-Adapter Male-Female	56	56	56	56	56	56	-	-	-	-
	Male Terminator Straight with LED	57	-	57	-	57	-	-	-	-	-
<b>Protection Cap</b>											
	Protection Cap for Male Connector							58-1			
	Protection Cap for Male Molded Cable Connector							59-1			
	Protection Cap for Male Panel-mount Connector							60-1			
	Protection Cap for Female Connector							58-2			
	Protection Cap for Female Molded Cable Connector							59-2			
	Protection Cap for Female Panel-mount Connector							60-2			